



TECHNICAL DATA		STANDARD				
<b>EXTERNAL DIMENSIONS</b>						
width		590 mm				
depth		600 mm				
height		850 mm				
<b>WEIGHT</b>		56,5 kg				
<b>VOLTAGE</b>		400V 3N 50Hz				
<b>POWER REQUIRED</b>		5150 W				
<b>WATER HARDNESS</b>		2-8 °F				
<b>INLET WATER PRESSURE</b>		200-400 kPa				
<b>CROCKERY DIMENSIONS</b>						
plates diameter		345 mm				
dishes max. height		320 mm				
<b>RACK DIMENSIONS</b>		500X500 mm				
<b>RACK EQUIPMENT</b>		1XC40 - 1XC44 - 1X15060				
<b>WASHING CYCLES</b>	(sec)	1(60)	2(90)	3(120)	4(180)	----
<b>WATER SUPPLY 55°C</b>						
racks/h(*) <sup>(1)</sup>		<b>60</b>	<b>40</b>	<b>30</b>	<b>20</b>	--
<b>WATER SUPPLY 10°C</b>						
racks/h(*) <sup>(1)</sup>		<b>20</b>	<b>20</b>	<b>20</b>	<b>20</b>	--
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)		2.3 L				
<b>BOILER CAPACITY</b>		5.7 L				
<b>BOILER HEATING ELEMENT</b>		4500 W				
<b>RINSING TEMPERATURE (SET)</b>		85°C				
<b>TANK CAPACITY</b>		29 L				
<b>TANK HEATING ELEMENT</b>		2700 W				
<b>TANK TEMPERATURE (SET)</b>		55°C				
<b>PUMP POWER</b>		650 W (340 L/min <sup>***</sup> )				
<b>DRAIN PUMP (optional)</b>		25 W h MAX draining 0.8m (40 L/min <sup>***</sup> )				
<b>NOISE</b>		63 dB(A)				

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.